




# State of the Art, Inc.

## M32159/05 Zero Ohm Chip Resistor

Surface Mount, Jumper



### FEATURES

- Operating temperature range : -55° C to +150° C
- MIL-PRF-55342 "S" level qualified manufacturer
- Solderable (termination material B) termination pretinned with SN60 over nickel barrier suitable for solder reflow vapor phase or wave solder attachment.
- Epoxy Bondable terminations available with silver based (C), platinum gold (U) and gold (G) finishes for epoxy attachment.

### PERFORMANCE


Termination Material	B/G	C	U
Maximum Resistance	0.035 Ω	0.050 Ω	0.175 Ω
Maximum Current	2.5A	2.1A	1.1A

Maximum Power Rating 225 mW

### ENVIRONMENTAL PERFORMANCE

Thermal Shock	Not to exceed maximum value
Low Temperature Operation	"
Short-time Overload	"
Resistance to Bonding Exposure	"
Moisture Resistance	"
High Temperature Exposure	"
Life	"

### POWER DERATING



Percentage of power to be applied at various ambient temperatures. Full rated power to 70°, linearly derated to 0 power at 150°C.

### PRODUCT LEVELS

All product levels are based on the same design. Level C is a Non-Established Reliability part requiring no group A, B or C testing. Military product level M is subject to group A, B and C testing per MIL-PRF-32159. Space product level T requires group A and B tests performed on a production lot basis, including 100% power conditioning.

### MECHANICAL

	INCHES	MILIMETERS
Length	.225 (.223 - .237)	5.72 (5.66 - 6.02)
Width	.070 (.070 - .080)	1.78 (1.78 - 2.03)
Thickness	.028 (.015 - .033)	0.71 (0.38 - 0.84)
Top Term	.020 (.015 - .025)	0.51 (0.38 - 0.64)
Bottom Term	.020 (.015 - .025)	0.51 (0.38 - 0.64)
Gap	.185 (.181 - .189)	4.70 (4.60 - 4.80)
Approx. Weight	.0262 grams	

Solderability: (Termination material (B) Solder coating compatible with Sn60, 62 or 63 solders, provides good wetting with all types of solder attachment. All product is tested IAW Mil-Std-202, method 208, including 8 hour steam aging.

### PART NUMBERING

M32159 B 05 M

PRODUCT LEVEL DESIGNATOR\*  
M: Military C: Industrial T: Space Level

Size Code: RCZ1505  
/05 = 0.225 X 0.070 X 0.025

Termination Material:  
B: Solderable  
C: Silver based epoxy bondable  
G: Gold epoxy bondable  
U: Pt Au epoxy bondable

### PACKAGING

Two packaging options are available:

Waffle Pack - (60 per Tray Max.)  
Tape & Reel - (4000 per 8" Inch Reel Max.)

### OPTIONS

SOTA offers a full line of thick & thin film resistors in the 2208 size including Standard Grade, High-Reliability (customer specified testing). Custom part marking is available.

STATE OF THE ART, INC. 2470 Fox Hill Road, State College, PA 16803-1797

Phone (814) 355-8004 Fax (814) 355-2714 Toll Free 1-800-458-3401

02/13/09

\*Specifications subject to change without notice.\*

Where Quality Isn't a Goal...It's Our Tradition